

Energy West Mining Company P. O. Box 310 15 No Main Street Huntington, UT 84528

C/015/0018

C/015/0018

C/015/0019

January 14, 2008

Ms. Pamela Grubaugh-Littig Permit Supervisor 1594 West North Temple, Suite 1210 Box 145801 Salt Lake City, Utah 84114-5801

Dear Ms. Grubaugh-Littig:

I am enclosing for submittal the 4th. Quarter Engineering Inspection Reports for Cottonwood/Wilberg/Des Bee Dove Waste Rock Site and the old Waste Rock Site. Also, the Deer Creek Waste Rock Site and Elk Canyon/Original Site are enclosed.

Sincerely,

John Christensen, P.E. Sr. Construction Engineer

Encls.

RECEIVED
JAN 2 2 2008

0/015/00/8

			······································
IMPOUNDMENT INSPECT	TION AND CERTIFIED REPORT		Page 1 of 2
Permit Number	ACT/015/018	Report Date	Dec. 21, 2007
Mine Name	Deer Creek Mine		
Company Name	Energy West Mining		
Impoundment	Impoundment Name	Mine Site Pond:	Waste Rock Pond:
Identification	Impoundment Number		
	UPDES Permit Number	UT-0023604-001	
	MSHA ID Number	N/A	N/A
3			
Inspection Date	12/13/07 Waste Rock	k Pond 12/10/07	
Inspected By	Rick Cullum / John Christensen		
Reason for Inspection (Annual, Quarterly or Other Periodic Inspection, Critical Installation, or Completion of Construction)  4th Quarter 2007 Inspection			spection

Describe any appearance of any instability, structural weakness, or any other hazardous condition.

# Mine Site Pond

Waste Rock Pond

Conditions, Comments Etc.

No hazards observed.

No hazards observed.

Required for an
impoundment which
functions as a
SEDIMENTATION POND.

Sediment storage capacity, including elevation of 60% and 100% sediment storage volumes, and, estimated average elevation of existing sediment.

	Mine Site Pond:	Waste Rock Pond:
60% Design Storage Capacity	1.87 A.F. at 7213.1 ft.	.59 A.F. at 6312.7 ft.
100% Sediment Capacity	3.12 A.F. at 7216.0 ft.	.98 A.F. at 6313.45 ft.

	Mine Site Pond	Waste Rock Pond
rinciple Spillway evation (F.A.S.L.):	7218.64	6318.0
ergency Spillway	7232.03	6318.0

## IMPOUNDMENT INSPECTION AND CERTIFIED REPORT

Page 1 of 2

Field Information. Provide current water elevation, whether pond is discharging, type and number of samples taken, monitoring/instrumentation information, inlet/outlet conditions, or other related activities associated with the pond including but not limited to sediment cleanout, pond decanting, embankment erosion/repairs, monitoring information, vegetation on outslopes of embankments, etc.

Mine	Si	te	P	ond	
			_		

Waste Rock Pond

Water Elevation

7227.47

None

Discharging

Yes

Never

Inlet, Outlet, Spillway

Conditions

Good

Good

Out slope Conditions

No Change

No Change

\*See "Hydrologic Monitoring Data" report submitted quarterly to DOGM for monitoring information.

## Mine Site Pond

#### Waste Rock Pond

Sediment Volume

1.25 A.F. @ 7211.6

None

Remaining Sediment Storage Capacity

.62 A.F.

0.59 A.F.

Water impounded

8.30 A.F.

NONE

Changes, Comments, etc.

The pond was cleaned in the second quarter

of 2007.

The pond was frozen at time of the inspection.

No change from last inspection.

Qualification Statement



I hereby certify that; I am experienced in the construction of impoundments; I am qualified and authorized under the direction of a Registered Professional Engineer to inspect the condition and appearance of impoundments in accordance with the certified and approved designs for this structure; that the impoundment has been maintained in accordance with approved design and meet or exceed the minimum design requirements under all applicable federal, state and local regulations; and, that inspections and inspection reports are made by myself and include any appearances of instability, structural weakness or other hazardous conditions of the structure affecting stability.

Signature:

Signature:

Date:

Date:

2/05/000g

	MIANT AND CHRESTER BERARM	li .	1 5 1 -6 5	
	TION AND CERTIFIED REPORT		Page 1 of 2  Dec. 21, 2007	
Permit Number	ACT/015/009	Report Date		
Mine Name	Trail Mountain Mine			
Company Name	Energy West Mining Compar	ny		
Impoundment Identification	Impoundment Name	Trail Mountain Mi	ne Pond:	
	Impoundment Number			
	UPDES Permit Number	UT-G04003-001		
	MSHA ID Number	N/A		
IMPOUNDMENT INS	PECTION			
Inspection Date	Dec. 10, 2007			
Inspected By	John Christensen / Rick C	Cullum		
	ion Other Periodic Inspection, or Completion of Construction)	4th Quarter 2007	Inspection	
Required for an impoundment which functions as a	2. Sediment storage capacity, volumes, and, estimated avo	~	50% and 100% sediment storage ing sediment.	
impoundment which		erage elevation of existi		
impoundment which functions as a	volumes, and, estimated avoidable of the state of the sta	erage elevation of existi		
impoundment which functions as a	volumes, and, estimated avoidable for the state of the st	erage elevation of existi 282 A.F. at 7182 47 A.F. at 7183.6		
impoundment which functions as a	volumes, and, estimated avoidable of the control of	erage elevation of existing 282 A.F. at 7182 A.F. at 7183.6		
impoundment which functions as a	volumes, and, estimated avenues of the sign storage Capacity 0.2 100% Sediment Capacity 0.4  3. Principle and emergency spanning of the spillway	erage elevation of existing 282 A.F. at 7182 47 A.F. at 7183.6  illway elevations.		
impoundment which functions as a	volumes, and, estimated avenues of the storage of t	erage elevation of existing 282 A.F. at 7182 47 A.F. at 7183.6  illway elevations.		

Page 1 of 2

4. Field Information. Provide current water elevation, whether pond is discharging, type and number of samples taken, monitoring/instrumentation information, inlet/outlet conditions, or other related activities associated with the pond including but not limited to sediment cleanout, pond decanting, embankment erosion/repairs, monitoring information, vegetation on outslopes of embankments, etc.

Water Elevation

7182.84 (Pond was frozen at the time of inspection)

Discharging

No

Inlet, Outlet

Conditions

Good

Slope conditions

Good

\*See "Hydrologic Monitoring Data" report submitted quarterly to DOGM for monitoring information.

5. Field Evaluation. Describe any changes in the geometry of the impounding structure, average and maximum depths and elevations of impounded water, estimated sediment or slurry volume and remaining storage capacity, estimated volume of water impounded, and any other aspect of the impounding structure affecting its stability or function which has occurred during the reporting period.

Sediment Volume

0.16 A.F.

Remaining Sediment Storage Capacity

0.122 A.F.

Water Impounded

0.18 A.F.

Changes, comments, etc.

Mining has seized at Trail Mtn. operations, only storm run off will run into the pond. The pond was

cleaned in 4th Quarter 2005.



I hereby certify that; I am experienced in the construction of impoundments; I am qualified and authorized under the direction of a Registered Professional Engineer to inspect the condition and appearance of impoundments in accordance with the certified and approved designs for this structure; that the impoundment has been maintained in accordance with approved design and meet or exceed the minimum design requirements under all applicable federal, state and local regulations; and, that inspections and inspection reports are made by myself and include any appearances of instability, structural weakness or other hazardous conditions of the structure affecting stability.

Signature:

ullun

Date:

Jucoure aprilogg

IMPOUNDMENT INSPECTION	ON AND CERTIFIED REPORT		Page 1 of 2
Permit Number	ACT/015/019	Report Date	Dec 21, 2007
Mine Name	Cottonwood/Wilberg		
Company Name	PacifiCorp		
Impoundment Name	North Pond	South Pond	Waste Rock Pond
Impoundment Number.			
UPDES Permit Number			
MSHA ID NUMBER		UT 0022896-003A	UT 0022896-005
	1211-UT-09-02052-02	1211-UT-09-02052-03	
IMPOUNDMENT INSPECTION			

Inspection Date	Dec. 10, 2007	
Inspected By Rick Cullum/ John Christensen		
	4th Quarter Inspection 2007	

1. Describe any appearance of any instability, structural weakness, or any other hazardous condition.

North Pond: No instabilities or weaknesses observed.

South Pond: No instabilities or weaknesses observed.

Waste Rock Site Pond: No instabilities observed.

Sediment storage capacity, including elevation of 60% and 100% sediment storage volumes, and, estimated average elevation of existing sediment.

	North Pond	South Pond	Waste Rock
Pond			
60% Design	.34 A.F.	.19 A.F.	1.45 A.F.
Storage Capacity	at 7351.0 ft.	at 7322.3 ft.	at 6761.5 ft.
100% Sediment	.56 A.F.	.32 A.F.	2.42 A.F.
Capacity	at 7354.83 ft.	at 7325.33 ft.	at 6765.3 ft.

Principle and emergency spillway elevations.

Principal	North Pond	South Pond	Waste Rock Pond
Spillway Elevation	7354.83	7325.33	6766.3
Emergency Spillway	7363.33	7334.2	6770.0

Field Information. Provide current water elevation, whether pond is discharging, type and number of samples taken, monitoring/instrumentation information, inlet/outlet conditions, or other related activities associated with the pond including but not limited to sediment cleanout, pond decanting, embankment erosion/repairs, monitoring information, vegetation on outslopes of embankments, etc.

	North Pond	South Pond	Waste Rock Pond
Water Elevation	DRY 7" SNOW	DRY 7" SNOW	DRY 7" SNOW
Discharging	NO	NO	No
Inlet/Outlet Condition	Good	Good	Good
Slope conditions	Good	Good	Good

\*See "Hydrologic Monitoring Data" report submitted to DOGM quarterly for monitoring

Field Evaluation. Describe any changes in the geometry of the impounding structure, average and maximum depths and elevations of impounded water, estimated sediment or slurry volume and remaining storage capacity, estimated volume of water impounded, and any other aspect of the impounding structure affecting its stability or function which has occurred during the reporting period.

	North Pond	South Pond	Waste Rock Pond
Sediment Volume	0.10 AF	0.00 AF	1.19 AF
Remaining Sediment Storage Capacity	0.24 AF	0.19 AF	.26 AF
Water Impounded	0.0 AF	0.0 AF	0.12 AF

## Changes, Comments,

The repairs to the North and South Ponds were completed in April and May 2007. During the repairs the remaining sediment was cleaned and hauled to the waste rock site.

THE COTTONWOOD MINE WAS IDLED IN 2001, SO THE ONLY WATER THAT REPORTS TO THE PONDS are RUN-OFF DURING A STORM EVENT.

#### Qualification Statement



I hereby certify that; I am experienced in the construction of impoundments; I am qualified and authorized under the direction of a Registered Professional Engineer to inspect the condition and appearance of impoundments in accordance with the certified and approved designs for this structure; that the impoundment has been maintained in accordance with approved design and meet or exceed the minimum design requirements under all applicable federal, state and local regulations; and, that inspections and inspection reports are made by myself and include any appearances of instability, structural weakness or other hazardous conditions of the structure affacting stability,

Signature: Signature:

Date: